REQUEST FOR REDUCED LEAD AND COP	PER TAP WATER MONITORING
System's Name: City of Fresno Water Division	Type: KT CWS T NTNCWS
Address: 1910 E. University Avenue Fresno, CA 93703-2988	Size: >100,000 10,001 to 100,000 3,301 to 10,000 501 to 3,300 101 to 500
Telephone number: (209) 498-4126	□ ≤100
System ID #: 10-007	
Contact Person: Martin McIntyre	<u>*</u>
periods ending December , 1993. The above named wat the system to reduce lead and copper tap water monitoring from: Biannual to Annual Annual to Triennial	er system nereby requests that the state permit
The results of all water quality parameter samples and lead at monitoring periods are enclosed. The data are summarized xxxxx	nd copper samples collected during each of the magex &x on file with EPA and CA DHS
SIGNATURE hart R. hothy	
Martin McIntyre Water System	ns Supervisor II
NAME TITLE	DATE



Water Division • 209-498-1458 1910 East University • Fresno, California 93703-2988

December 28, 1994



Mr. Patrick Chan United States Environmental Protection Agency 75 Hawthorne Street San Francisco, California 94105-3901

Dear Mr. Chan:

SUBJECT: SUMMER 1994 LEAD AND COPPER SAMPLING RESULTS

Attached are results of the lead and copper monitoring performed by the City of Fresno during the Summer 1994.

The City of Fresno's sample results did not exceed the action level for lead or copper with the 90th percentile samples.

The City of Fresno's water distribution system continues to be significantly below the EPA's action level for both lead and copper. Accordingly, it is requested that the next round of testing be resumed in the Summer of 1996, to monitor lead and copper for the EPA.

Sincerely,

DEPARTMENT OF PUBLIC UTILITIES

Martin R. McIntyre

Water Systems Manager

Last R. L.

Enclosures

cc: William T. Hetland, Public Utilities Director

Daniel L. Trafican, Assistant Public Utilities Directorl

Cindy Forbes, California Department of Health Services

CITY OF FRESNO WATER DIVISION LEAD AND COPPER RULE COMPLIANCE MONITORING RESULTS OF SUMMER 1994 MONITORING

INTRODUCTION

The United States Environmental Protection Agency (USEPA) promulgated National Primary Drinking Water Regulations for lead and copper monitoring on June 7, 1991, (56 FR26460), commonly referred to as the Lead and Copper Rule. This Rule requires that the City of Fresno monitor the water distribution system from the source to the point of delivery at the consumer's tap. Three specific monitoring protocols are included in the Lead and Copper Rule regulations:

- 1) First draw tap water monitoring for lead and copper
- 2) distribution system monitoring for various water quality parameters, and
- 3) source water monitoring for lead, copper, and various water quality parameters.

For the purposes of the Lead and Copper Rule monitoring requirements, the City of Fresno is classified as a large public water supplier. This classification is based upon the City's 98,000 service connections which supply potable water to some 450,000 customers.

SAMPLE SITE SELECTION

The City of Fresno utilized the same Tier 1-C sample pool of residences which were selected for the initial year of testing. (Two rounds of sampling and analysis for lead and copper were required for 1993 whereas only one round was required for 1994.) Eighteen of these residences were not sampled for 1994; two residents had installed water filtration/softening devices, seven

residents could not be contacted, and nine chose not to participate in this sampling. One resident had moved into another dwelling which met all the criteria for a sample site and was thus added to the sample pool. Samples were collected for 114 sites in the sample pool. Exhibit 1 presents the completed Sample Site Justification/Collection Method Certification form from the Lead and Copper Rule Guidance Manual. The residents performing the tap water sampling are listed in Table 1. Water quality sampling was performed at eight source locations and twenty-five distribution system locations. These water quality sample locations are in the same areas as the tap water sample sites and represent the sources and distribution system for all the tap water sample sites in the Tier 1-C sample pool. The locations of the water quality sample sites are listed in Table 2.

SAMPLE COLLECTION

The City of Fresno collected their 1994 samples in compliance with the Lead and Copper Rule during the period August 27 - September 15, 1994. Residents collecting tap water samples were given written instructions (Exhibit 2) along with their sample bottle.

TAP WATER SAMPLE RESULTS

Table 3 presents the results of the tap water analysis for lead and copper. The table lists the lead and copper concentrations in descending order. This was done in order to determine the 90th percentile levels as required by the Lead and Copper Rule.

Lead Results

The 90th percentile lead level was determined by multiplying the number of samples taken by 0.9

(114 x 0.9 = 103). The 90th percentile lead level for the City of Fresno samples is 0.0025 mg/L which is below the EPA action level of 0.015 mg/L. The laboratory analysis detection limit for lead is the following: values less than 0.001 mg/L are reported as 0 (zero); values between 0.0010 and 0.0049 are reported as 0.0025 mg/L; values greater than 0.005 mg/L are reported directly.

Copper Results

The 90th percentile copper level was determined in the same way as for lead. The 90th percentile copper level for the City of Fresno is 0.29 mg/L which is below the EPA action level of 1.3 mg/L. The laboratory analysis detection limit for copper is the following: values less than 0.01 mg/L are reported as 0 (zero); values between 0.010 and 0.049 mg/L are reported as 0.025 mg/L; values greater than 0.05 mg/L are reported directly.

DISTRIBUTION SYSTEM AND SOURCE SAMPLE RESULTS

Water quality analysis was performed on twenty-five distribution system locations and eight points of entry to the distribution system. The results of this analysis are summarized in Tables 4 and 5.

Both the lead and copper concentrations of the source water at all eight of the sample locations were 0 (zero) mg/L. The laboratory analysis detection limit for both lead and copper have both been previously explained.

FUTURE LEAD AND COPPER MONITORING

Upon completion of the second consecutive year of sampling for the Lead and Copper Rule, the City of Fresno's water distribution system continues to be significantly below the EPA's action level. Accordingly, it is requested that the next round of testing be resumed in the summer of 1996, to monitor lead and copper for the EPA.

94lead

	- · - r	
SAMPLE SITE JUSTIFICATION COL		
	THE PARTY OF THE P	December 6 as a second as a second

System's Name:	City of Fresno W	ater Division	be: XX CARS I HUNCARS
Address:	1910 E. Universi	ty Ave.	E: 87x >100,000
	Fresno, CA 9370	3	7 3301 to 10,000
	(# 4 st 2 mm) and the second and selection (# 5 to 5 Novel Act of Marie Action (# 5 to 5 novel and the selection)	(S)	☐ <100
Telephone number:	(209) 498-4136		0 3.00
	10-007		
System ID #:			
Contact Person:	Martin R. McInty	re	
THE RESULTS OF LEADOCUMENT	D AND COPPER TAP WATE	R SAMPLES MUST BE AT	TACHED TO THIS
	100	å ed samela	embed 114
of samples required		7 01 000 710	
TARGETING CRITERIA			
# of single-family structuration of the 1982 or lead bio	res with cooper pipes with lea es and/or lead/service lines (Tier 1)	114
H of multi family circumstan	es with copper pipes with lead se and/or lead service lines (solder installed	0
and seek in 2002 in 1818	copper pipes with lead solds	installed	
after 1962 or lead pag	es and/or lead service lines (Tier 2)	0
# of sites that contain co	oper pipes with lead solder in	stalled before 1983	0
(to de rased outh it ist	R condition has been exhibited		
		TOTAL	114
Explanation of Tier 2 and	d Tier 3 sites (adizon addition)	ii pages ii nacessary)	
LEAD SERVICE LINE S	ITES		
	be drawn from lead service		0
	zwn from lead service line sit	98	· 0
Difference (explain differ			
Method used to identify	load service line sites (attach	additional pages if necessar	አ):
	TER QUALITY PARAMETER	(WQP) SAMPLES MUST B	BE ATTACHED TO THIS
DOCUMENT	, max - v	s and GAW has a	omniae estrailu
of samples required to be collected	25	f of WQP tap a	ubmitted 25
# of WGP entry point a required to be collect		f of WGP entry collected and s	point samples actually ubmitted

CAMPLE SITE JUSTIFICATION COLLECTION METHOD CERTIFICATION

CERTIFICATION OF COLLECTION METHODS

Columny uses.

Each first draw tap sample for lead and copper is one ther in volume and has stood motionless in the plumbing system of each sampling site for at least six hours.

Each fact draw sample collected from a single-family residence has been collected from the cold water labour to be traced with the cold water

Each first draw sample collected from a non-residential building has been collected at an interior tap from which water is typically drawn for consumption.

हैं इस किस-किस प्राामक व्यक्तियार during an annual or triented monitoring period has been व्यक्तियाँ हैं। पीर तिवासिक वो प्राप्तक, प्राप्तक, प्राप्तक, प्राप्तक, प्राप्तक, प्राप्तक, प्राप्तक, प्राप्तक, प्राप्तक, प्राप्तक,

Each resident who volunteered to collect tap water samples from his or her home has been properly instructed by finsert water system's name; City of Fresno Water Division in the proper methods for collecting lead and copper samples. I do not challenge the accuracy of those sampling results. Enclosed is a copy of the material distributed to residents explaining the proper collection methods, and a list of the residents who performed sampling.

CHANGE OF SAMPLING SITE		
Original site address:		
New site address:		
Distance between sites (approximately):		
T argeting Criteria: NEW:	OLD:	•
Reason for change (attach additional pages	i I necessary) ;	
SIGNATURE To aut R. I. To	ty.	
Martin R. McIntyre	Water Systems Manager	12-28-94
NAME	ППЕ	DATE

DIRECTIONS--RESIDENT TAP SAMPLE COLLECTION PROCEDURES

These samples are being collected to determine the contribution of household fixtures and pipes and/or solder to the lead and copper levels in tap water. This sampling effort is required by the Environmental Protection Agency, and is being accomplished through the cooperation of homeowners and residents. The collection procedure is described in detail below:

- 1. On the day prior to collecting the sample thoroughly clean and remove all debris which may have accumulated inside the aerator of your kitchen tap water faucet. Run the tap for 1-2 minutes after cleaning so that no loose debris will impact sampling process.
- 2. <u>Do not use any water for 6-8 hours on your premises prior to sampling.</u> The Water Division recommends that either early mornings (after awakening) or early evenings (after returning from work) are the best sampling times to ensure that the proper water conditions exist.
- 3. The primary kitchen cold water faucet is to be used for sampling. The sample must be 100% from the cold water side of the tap; it can not be a mixture of water "dialed" from both hot and cold service lines. Place the open sample bottle below the faucet and gently open the cold water tap. Slowly fill the sample bottle to the base of the neck and turn off the water. It should take 45-60 seconds to fill the sample bottle.
- 4. Tightly cap the sample bottle and place in the plastic bag provided. Fill in the information requested below; sign the form and place in the plastic bag with the sample bottle. Please review the address label below at this time to ensure that all information contained on the label is correct.
- 5. Place the sample outside your home for pick-up by 9:00 AM.
- 6. Results from this monitoring effort will be provided to participating customers when reports are generated for the Environmental Protection Agency.

Please call Bill Dunn at 498-4136 if you have any questions regarding these instructions. TO BE COMPLETED BY RESIDENT AND RETURNED WITH SAMPLE:

Water was last used:	TIME	DATE
Sample was collected:	TIME	DATE
I have read the above directions and	have taken a tap sample in a	accordance with these directions.
PRINTED NAMEADDRESS		
TO BE COMPLETED BY WATER Sample picked up byh:\prd\sproj\wq\lead\94sample.wp	Note: 1 to 1 t	Date

TABLE 2 - Water Quality Parameter Sample Locations

Type of Location	System Identification Number	Location
Source	W-79	(b) (9)
Source	W-86	
Source	W-91	
Source	W-97	
Source	W-99	
Source	W-131	
Source	W-140	
Source	W-KVDS	
Distribution	D-31	(b) (6)
Distribution	D-34	
Distribution	D-36	
Distribution	D-66	
Distribution	D-68	
Distribution	D-69	
Distribution	D-70	
Distribution	D-76	
Distribution	D-79	
Distribution	D-81	
Distribution	D-82	
Distribution	D-116	
Distribution	D-117	
Distribution	D-126	
Distribution	D-128	
Distribution	D-129	
Distribution	D-130	
Distribution	D-133	
Distribution	D-134	
Distribution	D-155	
Distribution	D-156	
Distribution	D-158	
Distribution	D-159	
Distribution	D-181	
Distribution	D-202	

Table 3 - TAP WATER SAMPLE ANALYSIS - SUMMER 1994

Sample		Lead	Lead
No.		Ranking	mg/L
Size (person sit)			
154		132	0.012
4		131	0.006
132		130	0.006
135		129	0.006
93		128	0.005
175		127	0.005
1		126	0.003
2		125	0.003
11		124	0.003
46		123	0.003
56		122	0.003
65		121	0.003
74		120	0.003
75		119	0.003
78		118	0.003
90	***************************************	117	0.003
92		116	0.003
102		115	0.003
109		114	0.003
116		113	0.003
117		112	0.003
119		111	0.003
127		110	0.003
133		109	0.003
136		108	0.003
148		107	0.003
149		106	0.003
152		105	0.003
155		103	0.003
157	90th	103	
	90111	CHARLEST AND DESIGNATION OF THE PERSON OF TH	0.003
163		102	0.003
166		101	0.003
171		100	0.003
176		99	0.003
200		98	0.003
3		97	0
10		96	0
20		95	0
21		94	0
25		93	0
26		92	0
30		91	0
36		90	0
39		89	0
40		88	0
43		87	0
50		86	0
51		85	0

Table 3 - TAP WATER SAMPLE ANALYSIS - SUMMER 1994

52	84	0
54	83	0
55	82	0
57	81	
		0
58	80	0
60	79 78	0
61	/8	0
62	77	0
63	76	0
64	75 74	0
66	74	0
67	73 72	0
69	72	0
71	71 70	0
76	70	0
79	69	0
80	68	0
81	67	0
83	66	0
84	65	0
86	64	0
87	63	0
88	62	0
95	61	0
98	60	0
100	59	0
105	58	0
110	57	0
111	56	0
112	55	0
113	54	0
114	53	0
115	52	0
118	51	0
120	50	0
122	49	0
124	48	0
125	47	0
126	46	0
129	45	0
130	44	0
131	43	
134	42	0
137	41	0
139	40	0
140	39	0
141	38	0
142	37	0
143	36	0
144	35	0
145	34	0

Table 3 - TAP WATER SAMPLE ANALYSIS - SUMMER 1994

147 33 150 32 151 31 153 30 156 29 158 28 159 27 161 26 164 25 165 24 167 23 168 22 169 21 170 20 174 19 18 18 27 17	0 0 0 0 0 0 0 0 0 0
151 31 153 30 156 29 158 28 159 27 161 26 164 25 165 24 167 23 168 22 169 21 170 20 174 19 18 18	0 0 0 0 0 0 0 0
156 29 158 28 159 27 161 26 164 25 165 24 167 23 168 22 169 21 170 20 174 19 18 18	0 0 0 0 0 0 0 0
156 29 158 28 159 27 161 26 164 25 165 24 167 23 168 22 169 21 170 20 174 19 18 18	0 0 0 0 0 0 0
156 29 158 28 159 27 161 26 164 25 165 24 167 23 168 22 169 21 170 20 174 19 18 18	0 0 0 0 0 0
158 28 159 27 161 26 164 25 165 24 167 23 168 22 169 21 170 20 174 19 18 18	0 0 0 0 0 0
159 27 161 26 164 25 165 24 167 23 168 22 169 21 170 20 174 19 18 18	0 0 0 0 0
164 25 165 24 167 23 168 22 169 21 170 20 174 19 18 18	0 0 0 0
164 25 165 24 167 23 168 22 169 21 170 20 174 19 18 18	0 0 0 0
167 23 168 22 169 21 170 20 174 19 18 18	0 0 0
167 23 168 22 169 21 170 20 174 19 18 18	0 0
168 22 169 21 170 20 174 19 18 18	0
174 19	0
174 19	
174 19	
18 18	0
27 17	
41 11	
27 17 38 16	
41 15	
42 14	
48 13	
53 12	overhauer d
53 12 72 11	
72 11 89 10	
91 9	
103 8	
107 7	
108 6	
123 5 128 4	
123 5 128 4 146 3 172 2	
146 3	
172 2	
173 1	-

TABLE 3 - TAP WATER SAMPLE ANALYSIS - SUMMER 1994

Sample	Copper	Copper
No.	Ranking	mg/L
153	132	0.72
137	131	0.54
166	130	0.54
176	129	0.49
155	128	0.47
50	127	0.45
133	126	0.45
81	125	0.44
175	124	0.43
150	123	0.42
200	122	0.42
143	121	0.4
174	120	0.39
148	119	0.37
152	118	0.37
92	117	0.36
151	116	0.36
156	115	0.36
171	114	0.36
132	113	0.34
10	112	0.32
90	111	0.32
168	110	0.32
169	109	0.32
127	108	0.31
129	107	0.31
159	106	0.31
88	105	0.3
145	104	0.3
130	103	0.29
2	102	0.28
115	101	0.28
142	100	0.28
149	99	0.28
136	98	0.27
26	98	
51	96	0.26
	95	
102	97536780	0.26
65	94	0.25
135	93	0.25
1	92	0.24
83	91	0.24
164	90	0.24
139	89	0.23
46	88	0.22
78	87	0.22
79	86	0.22
93	85	0.22

TABLE 3 - TAP WATER SAMPLE ANALYSIS - SUMMER 1994

163	84	0.22
167	83	0.22
30	82	0.21
134	81	0.21
170	80	0.21
39	79	0.2
43	78	0.2
54	77	0.2
100	76	0.2
147	75	0.2
161	74	0.2
67	73	0.19
80	72	0.19
109	71	0.19
112	70	0.19
21	69	0.18
55	68	0.18
117	67	0.18
157	66	0.18
165	65	
		0.18
58	64	0.17
62	63	0.17
76	62	0.17
113	61	0.17
124	60	0.17
11	59	0.16
64	58	0.16
71	57	0.16
114	56	0.16
125	55	0.16
20	54	0.15
52	53	0.15
98	52	0.15
110	51	0.15
66	50	0.14
95	49	0.14
141	48	0.14
63	47	0.13
74	46	0.13
86	45	0.13
158	44	0.13
25	43	0.12
56	42	0.12
75	41	0.12
111	40	0.12
144	39	0.12
87	38	0.12
119	37	0.11
126	36	0.11
40	35	0.11
122	34	0.085
	J4	10.000

TABLE 3 - TAP WATER SAMPLE ANALYSIS - SUMMER 1994

36	33	0.08
61	32	0.08
120	31	0.073
4	30	0.07
131	29	0.07
57	28	0.068
3	27	0.062
69	26	0.06
60	25	0.025
84	24	0.025
105	23	0.025
116	22	0.025
118	21	0.025
140	20	0.025
154	19	0.025
18	18	
27	17	
38	16	
41	15	
42	14	
48	13	
53	12	
72	11	
89	10	
91	9	
103	8	
107	7	
108	6	
123	5	
128	4	
146	3	
172	2	
173	1	

TABLE 4 - DISTRIBUTION SYSTEM WATER QUALITY ANALYSIS Samples Taken 09/09/94 - 09/12/94

Sample	Alkalinity	Calcium		Temp.	Cond
No.	(mg/L CaCO3)	(mg/l)	ph	(deg C)	(mS/cm)
D-31	130	24	7.28	22.4	0.28
D-34	85	17	7.52	25.2	0.2
D-36	100	24	7.39	24.1	0.27
D-66	93	20	7.25	25.1	0.23
D-68	120	24	7.26	24.8	0.27
D-69	120	24	7.02	23.3	0.27
D-70	95	20	7.16	24.8	0.22
D-76	120	26	7.13	25.1	0.27
D-79	95	21	7.28	21.7	0.24
D-81	100	22	7.27	26.1	0.25
D-82	97	19	7.25	24.9	0.23
D-116	110	24	6.92	26.7	0.28
D-117	110	21	7.12	26.1	0.23
D-126	95	20	7.23	24.7	0.22
D-128	170	32	7	23.7	0.37
D-129	99	21	7.32	24.9	0.25
D-130	130	25	7.29	25.9	0.28
D-133	89	17	7.48	22.9	0.21
D-134	83	18	7.45	24.9	0.22
D-155	85	17	7.15	24.3	0.2
D-156	140	27	7.01	24.1	0.33
D-158	150	28	7	24.9	0.33
D-159	150	30	6.98	25.8	0.34
D-181	85	17	7.28	23.8	0.2
D-202	140	38	7.1	23.2	0.41
Average	111.64	23.04	7.21	24.5	0.26
Minimum	83	17	6.92	21.7	0.2
Maximum	170	38	7.52	26.7	0.41

TABLE 5. SOURCE WATER QUALITY ANALYSIS Samples Taken 09/16/94

Sample	Lead	Copper	Alkalinity	Calcium		Tomp	Cond.
11					-13	Temp.	
No.	(mg/L)	(mg/l)	(mg/L CaCO3)	(mg/L)	рН	(deg C)	(mS/cm)
W-79	0	0	120	26	7.38	22	0.3
W-86	0	0	130	28	7.35	22.7	0.3
W-91	0	0	100	22	7.53	21.9	0.25
W-97	0	0	130	28	7.36	22.5	0.32
W-99	0	0	87	17	7.73	22.5	0.22
W-131	0	0	99	19	7.76	24	0.22
W-140	0	0	120	39	7.15	23.9	0.45
WKVDS	0	0	100	25	7.42	23	0.25
-							
Average	0	0	110.75	25.5	7.46	22.81	0.289
Minimum	0	0	87	17	7.15	21.9	0.22
Maximum	0	0	130	39	7.76	24	0.45